

HIGH ACCURACY, HIGH RESOLUTION  
3D TERRESTRIAL LASER SCANNER SYSTEM

# LMS-Z390i

The terrestrial laser scanner system *RIEGL* LMS-Z390i consists of a highly accurate and fast 3D scanner, associated operating and processing software *RiSCAN PRO*, and a calibrated and definitely orientated high-resolution digital camera. The system provides data which lend itself to automatic or semi-automatic processing of scan data and image data to generate products such as textured triangulated surfaces or orthophotos with depth information.

The *RIEGL* LMS-Z390i is a rugged and fully portable sensor especially designed for the rapid and accurate acquisition of high-quality three dimensional images, providing a unique and unrivalled combination of wide field-of-view, high accuracy, and fast data acquisition.

A standard Windows notebook and the bundled software package *RiSCAN PRO* enable the user to instantly acquire high-quality 3D data in the field and provide a variety of registration, post processing, 3D data viewing and export functions .



- **Architecture & Facade Measurement**
- **As-Built Surveying**
- **Archaeology & Cultural Heritage Documentation**
- **Civil Engineering**
- **City Modeling**
- **Topography**

visit our webpage  
[www.riegl.com](http://www.riegl.com)



**RIEGL**  
LASER MEASUREMENT SYSTEMS

## System Key Performance Data



### Scanner Hardware LMS-Z390i

allows high-speed, high resolution and accurate 3D measurements

- Range up to 400 m @ Laser Class 1
- Repeatability up to 2 mm
- Measurement rate up to 11000 pts / sec
- Field of View up to 80° x 360°
- TCP/IP data interface, easily allowing wireless data transmission
- Operated by any standard PC or Notebook
- Fully portable, rugged & robust

### Software RiSCAN PRO

RIEGL software package for scanner operation and data processing



- Data archiving using a well-documented tree structure in XML file format
- Object VIEW / INSPECTOR for intelligent data viewing and feature extraction
- Straightforward Global Registration
- Interfacing to Post Processing Software

### Camera

provides high resolution calibrated color images



#### NIKON D200 / NIKON D100 / NIKON D70s:

- D200: 10.2 Megapixel (3.872 x 2.592 pixel)
- D100 / D70s: 6.1 Megapixel (3.008 x 2.000 pixel)
- Lens focal length: 14/20/28/35/50/85/180 mm
- USB interface, easily allowing wireless data transmission

or

#### CANON EOS 1Ds MARK II / CANON EOS 20D:


- EOS 1Ds MARK II:  
16.7 Megapixel (4.992 x 3.328 pixel)
- EOS 20 D: 8.2 Megapixel (3.504 x 2.336 pixel)
- Lens focal length: 20/28/35/50/85/200 mm
- EOS 1Ds MARK II: IEEE 1394 firewire interface  
EOS 20 D: USB interface, easily allowing wireless data transmission

### The combination of the key components

#### Scanner, Software and Camera results in

- Automatic generation of high resolution textured meshes
- Photorealistic 3D reconstruction
- Exact identification of details
- Automatic generation of 3D orthophotos
- Online position and distance measurements
- Online setting of any virtual point of view

## Principle of Scanner Operation




The **range finder electronics (1)** of the 3D scanner *RIEGL* LMS-Z390i is optimized in order to meet the requirements of high speed scanning (fast laser repetition rate, fast and highly accurate signal processing, and high speed data interface).

The *vertical deflection* ("line scan") of the **laser beam (2)** is realized by a **polygon (3)** with a number of reflective surfaces. For high scanning rates and/or a vertical scan angle  $q$  up to  $80^\circ$ , the polygonal mirror rotates continuously at adjustable speed. For slow scanning rates and/or small scanning angles, it is oscillating linearly up and down. The *horizontal scan* ("frame scan") is provided by rotating the complete **optical head (4)** up to  $360^\circ$ .

Scandata: RANGE, ANGLE, SIGNAL AMPLITUDE and optional **TIMESTAMP** are transmitted to a **laptop (6)** via **TCP/IP Ethernet Interface (5)**. **Camera (7)** data are fed into the same laptop via **USB/firewire interface (8)**.

The **RiSCAN PRO software (9)** allows the operator to perform a large number of tasks including sensor configuration, data acquisition, data visualization, data manipulation, and data archiving. RiSCAN PRO runs on platforms WINDOWS XP or 2000 SP2.

## Dimensional Drawings



Technical Data 3D Scanner Hardware **RIEGL LMS-Z390i**

Rangefinder performance

Eye safety class



according to IEC60825-1:1993+A1:1997+A2:2001  
The following clause applies for instruments delivered into the United States:  
Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant  
to Laser Notice No. 50, dated July 26, 2001.

Measurement range<sup>1)</sup>

for natural targets, r<sup>3</sup> 80 % up to 400 m  
for natural targets, r<sup>3</sup> 10 % up to 140 m

Minimum range for natural targets 1 m  
for reflector targets 2 m

Accuracy<sup>2)</sup> 6 mm

Repeatability<sup>2)</sup> 4 mm (single shot), 2 mm (averaged)

Measurement rate up to 11000 pts/sec @ low scanning rate (oscillating mirror)  
up to 8000 pts/sec @ high scanning rate (rotating mirror)

Laser wavelength near infrared

Beam divergence<sup>3)</sup> typ. 0.3 mrad

Scanner performance

Vertical (line) scan

Scanning range 0° to 80°  
Scanning mechanism rotating / oscillating mirror  
Scanning rate 1 scan/sec to 20 scans/sec @ 80° scanning range  
Angle stepwidth D J<sup>4)</sup> 0.002° £ D J £ 0.2°  
between consecutive laser shots  
Angular resolution 0.001°

Horizontal (frame) scan

Scanning range 0° to 360°  
Scanning mechanism rotating optical head  
Scanning rate<sup>5)</sup> 0.01 °/sec to 15 °/sec  
Angle stepwidth D j<sup>4)</sup> 0.002° £ D j £ 0.75°  
between consecutive scan lines  
Angular resolution 0.001°

Inclination Sensors integrated, for vertical scanner setup position<sup>6)</sup>

Internal Sync Timer (option) GPS-synchronized time stamping of scan data<sup>6)</sup>

General technical data

Interface: for configuration & data output Ethernet TCP/IP, 10/100 MBit/sec  
for configuration RS 232, 19.2 kBd  
for data output ECP standard (enhanced capability port) parallel

Power supply input voltage 12 - 28 V DC

Power consumption typ. 55 W max 68 W

Current consumption @ 12 V DC typ. 4.6 A max 5.7 A  
@ 24 V DC typ. 2.3 A max 2.85 A

Main dimensions 463 mm x 210 mm (length x diameter)

Weight approx. 15 kg

Temperature range 0°C to +40°C (operation), -10°C to +50°C (storage)

Protection class IP64, dust and splash-water proof

1) Typical values for average conditions. Maximum range is specified for flat targets with size in excess of the laser beam diameter and near to normal incidence of the laser beam. In bright sunlight, the operational range is considerably shorter than under an overcast sky.

2) One sigma @ 50 m range under RIEGL test conditions and vertical scanner setup position.

3) 0.3 mrad correspond to 30 mm increase of beamwidth per 100 m of range.

4) Selectable via Ethernet Interface or RS232.

5) Horizontal scan can be disabled, providing 2D-scanner operation.

6) Specifications to be found in separate datasheet.

Information contained herein is believed to be accurate and reliable. However, no responsibility is assumed by RIEGL for its use. Technical data are subject to change without notice. Preliminary Data sheet, LMS-Z390i, 19/03/2007



**RIEGL**  
LASER MEASUREMENT SYSTEMS  
[www.riegl.com](http://www.riegl.com)

RIEGL Laser Measurement Systems GmbH, A-3580 Horn, Austria  
Tel.: +43-2982-4211, Fax: +43-2982-4210, E-mail: [office@riegl.co.at](mailto:office@riegl.co.at)  
RIEGL USA Inc., Orlando, Florida 32819, USA  
Tel.: +1-407-248-9927, Fax: +1-407-248-2636, E-mail: [info@rieglusa.com](mailto:info@rieglusa.com)  
RIEGL Japan Ltd., Tokyo 1640013, Japan  
Tel.: +81-3-3382-7340, Fax: +81-3-3382-5843, E-mail: [info@riegl-japan.co.jp](mailto:info@riegl-japan.co.jp)